

A-1



TOOL

1. Hex Key
2. Special tool

(FOR LAUNCH.OMEGA.GILA-PRO.)
(GILA.VITA.NEON.191.777.)

A-2



Use 4mm Hex Key by turning counter clock-wise to loosen the bolt on the bottom of the fork.

(FOR LAUNCH.OMEGA.GILA-PRO.)
(GILA.VITA.NEON.191.777.)

A-3



Separate the Crown assy. From the outer casting.

(FOR LAUNCH.OMEGA.GILA-PRO.)
(GILA.VITA.NEON.191.777.)

A-7



Remove the compression rod from the top of the leg.

(FOR LAUNCH.OMEGA.GILA-PRO.)
(GILA.VITA.NEON.191.777.)

A-8



This is the parts after disassembly the fork.

(FOR LAUNCH.OMEGA.GILA-PRO.)
(GILA.VITA.NEON.191.777.)

A-4



(FOR LAUNCH.OMEGA.GILA-PRO.)
(GILA.VITA.NEON.191.777.)

A-5



Remove the spring adjuster and spring assembly.

(FOR LAUNCH.OMEGA.GILA-PRO.)
(GILA.VITA.NEON.191.777.)

A-6



Remove the spacer & bumper.

(FOR LAUNCH.OMEGA.GILA-PRO.)
(GILA.VITA.NEON.191.777.)

A-13



TOOL

1. Hex Key
2. Special tool
3. T shape bar

(FOR)
(TR-PRO.SOFI.TRENDY.790)

A-14



Use special tool by turning counter clock-wise to loosen the top cap.

(FOR)
(TR-PRO.SOFI.TRENDY.790)

A-15



Remove the adjuster and spring assembly.

(FOR)
(TR-PRO.SOFI.TRENDY.790)

A-19



Remove the compression rod from the top of the leg.

(FOR)
(TR-PRO.SOFI.TRENDY.790)

A-20



This is the parts after disassembly the fork.

(FOR)
(TR-PRO.SOFI.TRENDY.790)

A-16



Use T shape tool by turning counter clock-wise to loosen the assembly.

(FOR)
(TR-PRO.SOFI.TRENDY.790)

A-17



Separate the Crown assy. From the outer casting.

(FOR)
(TR-PRO.SOFI.TRENDY.790)

A-18



Remove the bumper from the compression rod.

(FOR)
(TR-PRO.SOFI.TRENDY.790)

B-1



Install the compression rod into the inner leg.

(FOR OMEGA.GILA-PRO.)
 (GILA.VITA.NEON.)

B-2



Install the bumper & spacer into the compression rod.

(FOR OMEGA.GILA-PRO.)
 (GILA.VITA.NEON.)

B-3



Install the adjuster and spring assembly into the leg.

(FOR OMEGA.GILA-PRO.)
 (GILA.VITA.NEON.)

B-4



Use special tool by turning clock-wise to tighten the adjuster.

(FOR OMEGA.GILA-PRO.)
 (GILA.VITA.NEON.)

B-5



Install the crown assembly into the casting.

(FOR OMEGA.GILA-PRO.)
 (GILA.VITA.NEON.)

B-6



Use 4mm Hex Key to tighten the bolt on the bottom of the fork .
 (For both side)

(FOR OMEGA.GILA-PRO.)
 (GILA.VITA.NEON.)

B-13



Install the compression rod into the inner leg.

(FOR)
(TR-PRO.SOFI.TRENDY.790)

B-14



Install the bumper into the compression rod.

(FOR)
(TR-PRO.SOFI.TRENDY.790)

B-15



Install the crown assembly into the casting.

(FOR)
(TR-PRO.SOFI.TRENDY.790)

B-16



Use T-shape tool by turning counter clock wise to tighten the compression rod with casting.

(FOR)
(TR-PRO.SOFI.TRENDY.790)

B-17



Install the adjuster and spring assembly.

(FOR)
(TR-PRO.SOFI.TRENDY.790)

B-18



Use special tool by turning clock-wise to tighten the adjuster.

(FOR)
(TR-PRO.SOFI.TRENDY.790)