



geometries



size	s	s'	tt	tt'	a	b	ht	ha	sa	rc	drop	fc	wb
time machine TT02													
S	532	508	528	520	116	28	105	72.0°	74.0°	399	69	584	973
M	553	530	548	540	121	28	125	72.5	74.0°	399	69	602	990
L	583	560	588	560	126	29	153	73.0°	74.0°	399	69	619	1008
XL	614	591	588	580	139	28	185	73.5°	74.0°	399	67	633	1023
pro machine SLC01													
47 cm	498	458	509	520	135	46	120	71.6°	74.5°	405	69	573	968
49 cm	503	463	519	530	136	46	125	71.7°	75.5°	405	69	582	977
51 cm	518	481	529	540	150	45	139	72.0°	73.5°	405	69	581	976
53 cm	535	498	538	550	156	48	157	72.5°	73.5°	405	69	587	982
55 cm	554	518	550	560	160	38	167	72.5°	73.3°	405	69	596	991
57 cm	584	550	567	575	170	29	187	73.0°	73.0°	407	69	603	1000
59 cm	603	571	578	585	175	25	204	73.0°	73.0°	407	69	613	1010
61 cm	623	589	583	590	180	26	225	73.0°	73.0°	407	69	618	1016
team machine SLT01													
47 cm	504	465	511	520	135	40	125	71.6°	74.5°	405	69	576	971
49 cm	504	465	521	530	136	40	125	71.7°	74.5°	405	69	585	980
51 cm	520	482	530	540	149	40	139	72.0°	73.5°	405	69	584	979
53 cm	537	499	540	550	154	40	157	72.5°	73.5°	405	69	589	984
55 cm	558	521	552	560	159	30	167	72.5°	73.3°	405	69	597	992
57 cm	586	552	569	575	168	20	187	73.0°	73.0°	407	69	605	1002
59 cm	604	570	579	585	173	20	204	73.0°	73.0°	407	69	615	1012
61 cm	625	590	584	590	179	20	225	73.0°	73.0°	407	67	620	1018
cross machine CX01													
50 cm	537	501	519	524	139	-20	125	70.5°	74.5°	428	59	592	1013
52 cm	556	522	540	540	144	0	125	71.0°	74°	428	59	599	1021
54 cm	576	544	551	550	158	3	140	71.5°	73°	428	59	596	1017
56 cm	596	564	567	565	163	6	160	71.5°	73°	428	59	611	1032
58 cm	615	583	582	579	167	11	180	71.5°	73°	428	59	627	1048
61 cm	631	599	597	595	178	5	210	71.5°	73°	428	59	642	1064
cross machine CX02													
50 cm	537	501	-	525	134	-	105	70.5°	74.5°	428	59	592	1013
52 cm	556	524	-	540	144	-	125	71.0°	74.0°	428	59	599	1020
54 cm	576	543	-	550	159	-	140	71.5°	73.0°	428	59	596	1017
56 cm	597	563	-	565	165	-	160	71.5°	73.0°	428	59	611	1032
58 cm	615	582	-	580	170	-	180	71.5°	73.0°	428	59	627	1048
61 cm	646	613	-	595	179	-	210	71.5°	73.0°	428	59	642	1064
road racer SL01													
49 cm	496	456	516	525	133	40	115	71.7°	74.5°	408	69	579	977
52 cm	525	485	535	545	145	40	140	72.5°	74.0°	408	69	589	987
54 cm	540	501	545	555	154	40	155	72.5°	73.5°	408	69	594	992
56 cm	565	526	562	570	158	30	170	72.5°	73.5°	408	69	610	1008
58 cm	597	559	574	580	170	20	190	73.0°	73.0°	408	69	610	1008
61 cm	629	591	589	595	179	20	220	73.5°	73.0°	408	69	620	1018
size	s	s'	tt	tt'	a	b	ht	ha	sa	rc	drop	fc	wb

size	s	s'	tt	tt'	a	b	ht	ha	sa	rc	drop	fc	wb
streetfire SS01													
S (46 cm)	461	419	511	528	136	80	120	72.5°	74.4°	407	70	575	972
M (48 cm)	477	436	531	548	144	81	135	73.0°	74.1°	407	70	590	987
L (52 cm)	520	479	547	565	161	81	175	73.5°	74.6°	410	70	596	996
XL (56 cm)	557	517	566	585	177	81	210	73.5°	73.0°	410	70	610	1010
streetfire SSX													
S (46 cm)	455	416	510	528	137	81	120	72.5°	74.5°	407	70	575	972
M (48cm)	475	438	531	549	145	78	135	73.0°	74.0°	407	70	592	987
L (52 cm)	515	478	546	565	163	80	175	73.5°	73.5°	410	70	595	995
XL (56 cm)	555	520	566	585	178	76	210	73.5°	73.0°	410	70	610	1010



size	s	s'	tt	tt'	a	b	ht	ha	sa	rc	drop	fc	wb
fourstroke fs01													
15"	382	332	526	550	-	-	120	71.0°	73.0°	448	-	-	1082
17"	410	363	545	569	-	-	125	71.0°	73.0°	448	-	-	1102
19"	460	418	565	588	-	-	140	71.0°	73.0°	448	-	-	1133
21"	501	461	596	618	-	-	150	71.0°	73.0°	448	-	-	1152
fourstroke fs02													
17"	410	364	545	569	-	-	125	71.0°	73.0°	448	5	634	1082
19"	460	415	564	588	-	-	140	71.0°	73.0°	448	5	653	1102
21"	501	456	596	618	-	-	150	71.0°	73.0°	448	5	684	1133
23"	540	494	618	637	-	-	165	71.0°	73.0°	448	5	703	1151
fourstroke fs03													
17"	410	363	545	567	106	185	125	71.0°	73.0°	448	5	634	1082
19"	460	418	565	588	128	163	140	71.0°	73.0°	448	5	654	1102
21"	501	461	596	618	135	128	150	71.0°	73.0°	448	5	684	1133
23"	540	505	620	637	148	99+	165	71.0°	73.0°	448	5	704	1152
trailfox tf01 02													
17"	410	360	548	570	108	190	125	69.0°	72.5°	457	5	650	1107
19"	460	415	566	591	125	154	140	69.0°	72.5°	457	5	672	1129
21"	501	460	595	620	138	123	150	69.0°	72.5°	457	5	701	1159
23"	540	503	621	643	147	97	165	69.0°	72.5°	457	5	725	1182
supertrail st01													
17"	410	360	-	560	-	-	125	68.0°	72.0°	449	5	649	1098
19"	460	411	-	585	-	-	140	68.0°	72.0°	449	5	676	1124
21"	500	452	-	610	-	-	150	68.0°	72.0°	449	5	701	1150
23"	540	492	-	635	-	-	165	68.0°	72.0°	449	5	728	1176

team elite te01													
16"	407	371	550	575	164	-	130	71.0°	73.0°	425	32	631	1054
18"	458	421	565	590	165	-	140	71.0°	73.0°	425	32	645	1068
20"	508	472	585	605	165	-	165	71.0°	73.0°	425	32	660	1083
22"	552	522	603	615	167	-	150	71.0°	73.0°	425	32	671	1094
team elite j24													
15"	381	338	499	521	154	-	140	70.0°	73.0°	410	25	580	989
team elite te02													
16"	407	366	550	575	164	-	130	71.0°	73.0°	425	32	630	1054
18"	457	419	564	590	165	-	140	71.0°	73.0°	425	32	644	1068
20"	508	470	585	605	165	-	140	71.0°	73.0°	425	32	660	1084
22"	559	522	603	615	167	-	150	71.0°	73.0°	425	32	671	1094

virus 01 02 03														
15"	381	336	540	564	110	98	175	71.0°	73.0°	425	32	614	1034	– 160 cm
17"	432	387	556	582	120	113	138	71.0°	73.0°	425	32	632	1055	160 – 170 cm
19"	483	438	571	594	130	128	100	71.0°	73.0°	425	32	645	1068	170 – 180 cm
21"	534	488	584	602	150	143	71	71.0°	73.0°	425	32	653	1076	180 – 188 cm
23"	584	539	605	617	170	158	43	71.0°	73.0°	425	32	669	1092	188 – 205 cm
size	s	s'	tt	tt'	a	b	ht	ha	sa	rc	drop	fc	wb	