



FELT
06MTB&SHOT

RIDER:

Those seeking one of the lightest, fastest, most comfortable, most energy-efficient, most technologically advanced XC production bikes the world has ever seen.

FRAME:

Felt Proprietary Superlight Easton Scandium Tubing / Felt Exclusive Carbon Fiber Seatstays, Cold Forged Dropouts, Replaceable Derailleur Hanger, Fully-Integrated Head Tube

FORK:

Fox F80X w/Terra Logic Inertia Valve, Rebound & Bump Threshold Adjustment, 80mm Travel

GROUP:

Shimano XTR Front & Rear Derailleurs, Cranks, Cassette, and V-Brakes/Levers; XT Rapid Fire Shifters; Dura-Ace Chain

WHEELSET:

Mavic CrossMax SL Tubeless;
Hutchinson Bulldog UST Tubeless Tires 26 x 2.1

COMPONENTS:

Carbon-Wrapped Aluminum Handlebar, Stem and Seatpost; Carbon Shell Saddle
w/ Superlite Foam and CrN/Ti Rails

WEIGHT:

20.9 lbs (17.5")

FINISH: Matte Black

SIZES: 15.5, 17.5, 19.5, 21.5



FINISH: Brushed Silver

SIZES: 15.5, 17.5, 19.5, 21.5

06RXC PRO

RIDER:

Those demanding disc brake performance and who are well aware that races can indeed be won without full XTR.

FRAME:

Felt proprietary Superlight 7000 Series Aluminum Tubing / Felt Exclusive Carbon Fiber Seatstays, Cold Forged Dropout, Replaceable Derailleur Hanger, Fully-Integrated Head Tube

FORK:

Answer/Manitou R7 w/Remote Lockout, 80mm Travel

GROUP:

Shimano XTR Rear Derailleur; XT Cranks, Front Derailleur, Rapid Fire Shifters, Cassette

WHEELSET:

Mavic Crossride; Hutchinson Bulldog Folding-Bead Tires 26 x 2.1

COMPONENTS:

Hayes HFX-9 Carbon Disc Brakes, Butted Aluminum Riser Handlebar, 4-Bolt Cold-Forged + CNC Aluminum Stem, 2-Bolt Aluminum Seatpost, Felt Form Race Saddle w/Superlite Foam, Kevlar Corners & Cr-Mo Rails.

WEIGHT:

23.7 lbs (17.5")



06RXCELITE

RIDER:

Disc brake riders looking for outstanding overall value, yet do not underestimate the importance of a high-quality frameset.

FRAME:

Felt proprietary Superlight 7000 Series Aluminum Tubing / Felt Exclusive Carbon Fiber Seatstays, Cold Forged Dropouts, Replaceable Derailleur Hanger, Semi-Integrated Head Tube

FORK:

RockShox J3 Magnesium w/Lockout, 80mm Travel

GROUP:

Shimano XT Rear Derailleur; LX Front Derailleur, Deore Rapid Fire Shifters & Cassette

WHEELSET:

Alex Double-Wall Disc Rims, Formula Hubs, 15G Black Stainless Spokes; Hutchinson Bulldog Folding-Bead Tires 26 x 2.1

COMPONENTS:

Hayes HFX-9 Disc Brakes, Truvativ Firex SX Giga-X-Pipe 2-Piece Crankset w/External Bearings, Butted Aluminum Riser Handlebar, 4-Bolt Cold-Forged + CNC Aluminum Stem, Felt Form Sport Saddle.

WEIGHT:

26.5 lbs (17.5")

FINISH: Matte Pewter

SIZES: 15.5, 17.5, 19.5, 21.5



FINISH: Red

SIZES: 15.5, 17.5, 19.5, 21.5

06RXC

RIDER:

Those who demand all the features that only an RXC frameset can offer, as well as a component package targeting exceptional performance and value.

FRAME:

Felt proprietary Superlight 7000 Series Aluminum Tubing / Felt Exclusive Carbon Fiber Seatstays, Cold Forged Dropouts, Replaceable Derailleur Hanger, Semi-Integrated Head Tube

FORK:

RockShox J3 Magnesium w/Lockout, 80mm Travel

GROUP:

Shimano XT Rear Derailleur; LX Front Derailleur, Deore Rapid Fire Shifters, Hubs, Cassette, & V-Brakes

WHEELSET:

Alex Doublewall 32H Rims, Shimano Deore Hubs, 15G Black Stainless Spokes, Hutchinson Bulldog Folding-Bead Tires 26 x 2.1

COMPONENTS:

Truvativ Firex SX Giga-X-Pipe 2-Piece Crankset w/External Bearings, Butted 6061 Aluminum Handlebar, 4-Bolt Cold-Forged Aluminum Stem, Felt Form Sport Saddle

WEIGHT:

25.1 lbs (17.5")



JUMP SHOT

RIDER:

Dirt Jump specific. Those who do not see a bike as transportation.

FRAME:

Felt Jump Shot with Eccentric BB Set, 6061 Butted Aluminum Tubing with Custom Hydroformed Top Tube

FORK:

Marzocchi Dirt Jam Comp, Coil + MCU Spring, 100mm Travel

GROUP:

Truvativ Hussefelt Cranks, Acs Cr-Mo 16T Freewheel, KMC 1/2 x 1/8" BMX Chain

WHEELSET:

Alex Double-Wall Rims w/Stainless Steel Eyelets, Felt 4-Bearing Hubs, Tioga Yellow Kirin 26 x 2.3" Tires

COMPONENTS:

Hayes Mechanical Disc Brake, Truvativ Hussefelt Handlebar & Stem, Felt Jump Saddle

WEIGHT:

31 lbs

FINISH: Matte Red

SIZES: 15.5 only



FINISH: Matte Black

SIZES: 15.5 only

STRAIGHT SHOT

RIDER:

Those who choose to climb their way to the top, before engaging in fast descents, big hits, and sizable drops.

FRAME:

Felt Shot Design, 6061 Butted Aluminum Tubing with Custom Hydroformed Top Tube, Euro BB set w/ISCG Mount

FORK:

Manitou Stance, Coil Spring, FFD Damping, 130mm Travel

GROUP:

Truvativ Hussefelt Cranks & ISCG Boxguide, Sram X.7 Trigger Shifter & 5.0 Rear Derailleur

WHEELSET:

Alex Double-Wall Rims w/Stainless Steel Eyelets, Felt 4-Bearing Hubs, Tioga Yellow Kirin 26 x 2.3" Tires

COMPONENTS:

Hayes Hydraulic Disc Brakes, Truvativ Hussefelt Handlebar & Stem, Felt MTB Saddle w/Cr-Mo Rails

WEIGHT:

32.4 lbs



DOUBLESHOT

RIDER:

Those seeking the ultimate in spec value and a wider gear selection, demanding no less than the best when it comes to the frame.

FRAME:

Felt Shot Design, 6061 Butted Aluminum Tubing with Custom Hydroformed Top Tube, Euro BB set w/ISCG Mount

FORK:

SR/Suntour XCP-75DJ, Coil Spring, 120mm Travel

GROUP:

SR/Suntour Duro-D Cranks w/Double Chainwheel, Sram X.7 Trigger Shifter w/5.0 Rear Derailleur

WHEELSET:

Alex Double-Wall Disc Rims, Felt Disc Hubs with Q/R Axle Design, Tioga Yellow Kirin 26 x 2.3" Tires

COMPONENTS:

Hayes Mechanical Disc Brakes, Truvativ Hussefelt Handlebar & Stem, Felt MTB Saddle

WEIGHT:

32 lbs

FINISH: Matte White

SIZES: 15.5 only



06SPECIFICATIONS

SHOT

MODEL	JUMP SHOT	STRAIGHT SHOT	DOUBLE SHOT
COLORS	Matte Red	Matte Black	Matte White
SIZES	15.5"	15.5"	15.5"
FRAME	Felt Shot Eccentric Design, 6061 Aluminum, Hydroform Top Tube, 565mm TTL with USA B8 Shell & Eccentric B8 Set	Felt Shot Design, 6061 Aluminum, Hydroform Top Tube, with Euro B8 Shell, Replaceable Derailleur Hanger, ISCG Chainguide Mount	Felt Shot Design, 6061 Aluminum, Hydroform Top Tube, with Euro B8 Shell, Replaceable Derailleur Hanger, ISCG Chainguide Mount
FORK	Marzocchi Dirt Jam Comp, 100mm Travel, Coil+MCU Spring, Magnesium Lowers, 32mm Stanchions, 6" IS Disc Mount, External Preload Adjust	Answer Slance / Blunt, 130mm Travel, Coil Spring, FFD Damping, Magnesium Lowers, 32mm Black Nitride Cr-Mo Stanchions, Post-Type Disc Mount	SR / Suntour XCP75-DJ, 120mm Travel, Coil Spring, Magnesium Lowers, 30mm Stanchions, IS Disc Mount
HEADSET	Semi-Integrated 1-1/8" Aheadset	Semi-Integrated 1-1/8" Aheadset	Semi-Integrated 1-1/8" Aheadset
STEM	Truvativ Hussefelt Forged Aluminum 4-Bolt Design, 31.8mm Bar Clamp, 7 Degree Rise, 40mm Extension, Sandblast Black Anodized	Truvativ Hussefelt Forged Aluminum 4-Bolt Design, 31.8mm Bar Clamp, 7 Degree Rise, 40mm Extension	Truvativ Hussefelt Forged Aluminum 4-Bolt Design, 31.8mm Bar Clamp, 7 Degree Rise, 40mm Extension
HANDLEBAR	Truvativ Hussefelt 31.8mm AL-66 Riser 50mm x 640mm	Truvativ Hussefelt 31.8mm AL-66 Riser 25mm x 680mm	Truvativ Hussefelt 31.8mm AL-66 Riser 25mm x 680mm
GRIPS	Felt Single-Density 130mm L x 30mm OD	Felt Single-Density 130mm L x 30mm OD	Felt Single-Density 130mm L x 30mm OD
BAR END CAPS	Felt Handi-Caps Alloy	Felt Handi-Caps Alloy	N/A
SHIFTERS	N/A	SRAM X.7 Trigger 8-SP	SRAM X.7 Trigger 8-SP
F/DER	N/A	N/A	Sram 3.0
CHAINGUIDE	N/A	Truvativ Hussefelt Boxguide, ISCG Mount	N/A
R/DERAILLEUR	N/A	SRAM 5.0 ESP	SRAM 5.0 ESP
CRANKSET	Truvativ Hussefelt Heat-Treated Steel 32T Single Chaining, 170mm	Truvativ Hussefelt, 38T Single Chaining, 170mm	SR / Suntour Dura-D Aluminum Arm, Double Steel Chaining 32/22T, 170mm
BB SET	Truvativ Giga Pipe DH ISIS Drive, AL Cups	Truvativ Giga Pipe DH ISIS Drive, AL Cups	TH ISIS Drive, ST Cups
CHAIN	KMC Z610HX	KMC Z72	KMC Z72
FREEWHEEL	ACS Claws 1/2x3/32x16T	SRAM PG-850 PG II, 8-SP 11-32T	SRAM PG-850 PG II, 8-SP 11-32T
PEDALS	Felt Backpedal Alloy Platform	Felt Backpedal Alloy Platform	Felt Backpedal Alloy Platform
CABLES	Felt Black w/Rubber Tube Tops	Felt Black w/Rubber Tube Tops	Felt Black w/Rubber Tube Tops
BRAKE LEVERS	Hayes	Hayes	Hayes
BRAKES	Hayes MX-ZXC Mechanical 6" Rotor RR Only	Hayes HFX-9 Hydraulic, Rotors: 8" FT, 6" RR	Hayes MX-1 Mechanical, Rotors: 8" FT, 6" RR
SADDLE	Felt Dirt Jump, Cr-Mo Rails	Felt Form Race, 7mm Cr-Mo Rails	Felt Form Sport, 7mm Rails
SEAT POST	Truvativ XRDC Double-Bolt, 31.6mm x 250mm	Truvativ XRDC Double-Bolt, 31.6mm x 350mm	Truvativ XRDC Double-Bolt, 31.6mm x 350mm
SEAT POST CLAMP	Quick-Release-Type Cold Forged 6061 Aluminum, 31.8mm	Quick-Release-Type Cold Forged 6061 Aluminum, 31.8mm	Quick-Release-Type Cold Forged 6061 Aluminum, 31.8mm
F/HUB	Felt Cold-Forged Aluminum Body 36H, with 3-Piece Bolted Axle	Felt Cold-Forged Aluminum Body 36H, with 3-Piece Bolted Axle	Felt Cold-Forged Aluminum Body 36H, with Alloy Quick Release
R/HUB	Felt Double-Drive, Spin-On FW Type, Cold-Forged Aluminum Body, 4-Bearing, 36H, with 3-Piece Bolted Axle	Felt 8-Speed Cassette Type, Cold-Forged Aluminum Body, 4-Bearing, 36H, with 10mm Nutted Thru Axle	Felt 8-Speed Cassette Type, Cold-Forged Aluminum Body 36H, with Alloy Quick Release
RIMS	Alex Supra BH Disc 36H 32mm Wide w/SS Eyelets	Alex Supra BH Disc 36H 32mm Wide w/SS Eyelets	Alex Supra FP28 Disc 36H 28mm Wide
TIRES	Tioga Yellow Kirin 26 x 2.3 60TPI Kevlar Bead	Tioga Yellow Kirin 26 x 2.3 60TPI Kevlar Bead	Tioga Yellow Kirin 26 x 2.3 Wire Bead
SPOKES	Black Stainless 146, Brass Nipples	Black Stainless 146, Brass Nipples	Black Stainless 146, Brass Nipples

RXC

MODEL	RXC	RXC Elite	RXC Pro	RXC Team
COLORS	Red	Matte Pewter	Brushed Silver	Matte Black
SIZES	15.5, 17.5, 19.5, 21.5"	15.5, 17.5, 19.5, 21.5"	15.5, 17.5, 19.5, 21.5"	15.5, 17.5, 19.5, 21.5"
FRAME	Felt Superlight XC Series 6061 Double-Butted Aluminum, with Carbon Fiber Seat Stays, Semi-Integrated Head Tube, V-Brake Specific	Felt Superlight XC Series 6061 Double-Butted Aluminum, with Carbon Fiber Seat Stays, Semi-Integrated Head Tube, Disc-Brake Specific	Felt Superlight XC Series 6061 Double-Butted Aluminum, with Carbon Fiber Seat Stays, Integrated Head Tube, Disc-Brake Specific	Felt Superlight XC Series Easton Scandium, with Carbon Fiber Seat Stays, Integrated Head Tube, V-Brake Specific
FORK	RockShox J3 w/ TurnKey Lockout, Magnesium Lowers, 28mm 4130 Cr-Mo Stanchions, Preload Adjust, 80mm Travel	RockShox J3 w/ TurnKey Lockout, Magnesium Lowers, 28mm 4130 Cr-Mo Stanchions, Preload Adjust, 80mm Travel	Manitou R7 w/ClickIt Remote Lockout, 30mm Aluminum Stanchions, Magnesium Lower Air Spring, 80mm Travel, w/External Rebound Adjust	Fox F80X, Butted AL Steer Tube, AL Stanchions, Magnesium Lower, Air Spring, 80mm Travel, w/TerraLogic Inertia Valve, w/Rebound & Bump Threshold Adjust
HEADSET	Semi-Integrated 1-1/8" Aheadset	Semi-Integrated 1-1/8" Aheadset	Integrated 1-1/8" Aheadset-Cane Creek Type 45 Degree Sealed Cartridge Bearing	Integrated 1-1/8" Aheadset-Cane Creek Type 45 Degree Sealed Cartridge Bearing
STEM	One-Piece Cold-Forged 6061 Aluminum, 4-Bolt, 5 Degree. Extensions: 13.5=90mm; 15.5=100mm; 17.5=110mm; 19.5=120mm; 21.5=130mm	One-Piece Cold-Forged 6061 Aluminum, 4-Bolt, 5 Degree. Extensions: 13.5=90mm; 15.5=100mm; 17.5=110mm; 19.5=120mm; 21.5=130mm	One-Piece Cold-Forged 6061 Aluminum, 4-Bolt, 5 Degree. Extensions: 13.5=90mm; 15.5=100mm; 17.5=110mm; 19.5=120mm; 21.5=130mm	One-Piece Cold-Forged Carbon-Wrapped 2014 Aluminum, 4-Bolt, 5 Degree. Extensions: 13.5=90mm; 15.5=100mm; 17.5=110mm; 19.5=120mm; 21.5=130mm
HANDLEBAR	Butted 6061 Aluminum, Flatbar, 4 Degree Bend, Widths: 13.5=540mm, 15.5=580mm; 19.5=600; 21.5=620	Butted 6061 Aluminum, 30mm Rise, 6 Degree Bend, Widths: 13.5=580mm, 19.5=600; 21.5=620	Butted 6061 Aluminum, 30mm Rise, 6 Degree Bend, Widths: 13.5=580mm, 19.5=600; 21.5=620	Carbon-Wrapped Butted 7075 Aluminum, Flatbar, 6 Degree Bend, Widths: 13.5=540mm; 15.5=580mm; 19.5=600; 21.5=620
GRIPS	Felt Single-Density 130mm L x 30mm OD	Felt Single-Density 130mm L x 30mm OD	Felt Single-Density 130mm L x 30mm OD	Felt Single-Density 130mm L x 30mm OD
SHIFTERS	Shimano Deore Rapidfire, 27-Speed	Shimano Deore Rapidfire, 27-Speed	Shimano M751 Rapid Fire Shifter, 27-Speed	Shimano M751 Rapid Fire Shifter, 27-Speed
FRONT DER	Shimano Deore LX	Shimano Deore LX	Shimano Deore XT	Shimano XTR
REAR DER	Shimano Deore XT, Top-Normal M751	Shimano Deore XT, Top-Normal M751	Shimano XTR SGS Top-Normal M952	Shimano XTR SGS Top-Normal M952
CRANKSET	Truvativ Firex SX, Cold-Forged AL-66, Giga-X-Pipe, 44/32/22T, 7075 Outer Ring	Truvativ Firex SX, Cold-Forged AL-66, Giga-X-Pipe, 44/32/22T, 7075 Outer Ring	Shimano Deore XT Hollowtech II 44/34/24T	Shimano XTR Hollowtech II 44/32/22T
BB SET	Included with Crankset	Included with Crankset	Included with Crankset	Included with Crankset
FW	Shimano Deore 11-32T	Shimano Deore 11-32T	Shimano XT 11-34T	Shimano XTR 11-34T
CHAIN	Sram PC-951	Sram PC-951	Sram PC-951	Shimano CN-7701
BRAKE LEVERS	Shimano Deore	Hayes Alloy	Hayes Carbon	Shimano XTR
BRAKES	Shimano Deore V-Brake	Hayes HFX 9 XC Hydraulic, V6 160mm Rotors	Hayes HFX 9 XC Carbon, V6 160mm Rotors	Shimano XTR V-Brake
CABLES	Felt Amber/Gray Weave w/CP Stamped Logos	Brake: Hayes, Derailleur: Felt Black w/CP Stamped Logos	Brake: Hayes, Derailleur: Felt Black w/CP Stamped Logos	Shimano XTR
SADDLE	Felt "Form" Sport w/Tough Corners, 7mm Rails	Felt "Form" Sport w/Tough Corners, 7mm Rails	Felt "Form" Race Superlight Foam, w/Kevlar Corners, Tubular Cr-Mo 7mm Rails	Felt "Form" Ultra-Light Carbon Base, Super-Lightweight Foam, CN/Ti Rails
SEAT POST	Alloy Micro-Adjust, Low-Profile Head, 27.2mm x 350mm	Alloy Micro-Adjust, Low-Profile Head, 27.2mm x 350mm	Alloy 2-Bolt Micro-Adjust, Low-Profile Head, 27.2mm x 350mm	Carbon-Wrapped 2014 Forged Alloy 2-Bolt Micro-Adjust, 27.2mm x 350mm
SEAT POST CLAMP	Felt Bolt-Type, Cold Forged, 4061 AL, w/Barrel Nut, 30.6mm	Felt Bolt-Type, Cold Forged, 4061 AL, w/Barrel Nut, 30.6mm	Felt Bolt-Type, Cold Forged, 4061 AL, w/Barrel Nut, 30.6mm	Felt Bolt-Type, Cold Forged, 4061 AL, w/Barrel Nut, 30.6mm
F/HUB	Shimano Deore	Formula Cold-Forged Aluminum Body 32H	Mavic CrossRide Wheelset	Mavic CrossMax SL Tubeless Wheelset
R/HUB	Shimano Deore	Formula Cold-Forged Aluminum Body 32H	Mavic CrossRide Wheelset	Mavic CrossMax SL Tubeless Wheelset
RIMS	Alex ACE-18 Doublewall, 22mm Wide, 32H w/CNC Sidewalls	Alex TD-17 Doublewall Disc-Type, 22mm Wide, 32H	Mavic CrossRide Wheelset	Mavic CrossMax SL Tubeless Wheelset
TIRE	Hutchinson Bulldog 26 x 2.1, FT/RR, 66TPI Folding Bead, Superlight 115g Tubes	Hutchinson Bulldog 26 x 2.1, FT/RR, 66TPI Folding Bead, Superlight 115g Tubes	Hutchinson Bulldog 26 x 2.1, FT/RR, 66TPI Folding Bead, Superlight 115g Tubes	Hutchinson Bulldog 26 x 2.1, FT/RR, 66TPI Folding Bead, Superlight 115g Tubes
SPOKES	15G Stainless	15G Stainless	Wheelset	Wheelset
PEDALS	Low-Profile, Alloy Cage / Alloy Body, 255g	Low-Profile, Alloy Cage / Alloy Body, 255g	none	none

06GEOMETRY

RXC TEAM

SIZE	A. HA	B. SA	C. TTL (HORIZONTAL)	D. TTL (C TO C)	E. HEAD TUBE LENGTH	F. ST LENGTH (C TO T)	G. ST LENGTH (C TO C)	H. BB DROP	I. CHAINSTAY LENGTH	J. FRONT CENTER	K. WHEEL BASE	L. STANDOVER	CRANK LENGTH	STEM	H-BAR	SEATPOST SIZE
15.5	71.0	74.5	560	546.3	120	394	333.1	40	426	623.9	1046.7	701	172.5	100	580 x 0rise	350 x 27.2
17.5	71.0	73.0	590	564.3	120	445	386.2	40	422	638.7	1057.5	731	175	110	580 x 0rise	350 x 27.2
19.5	71.0	73.0	620	596.1	130	495	437.4	40	422	669	1087.9	766	177.5	120	600 x 0rise	350 x 27.2
21.5	71.0	72.5	635	614.4	150	546	489.3	40	422	679.4	1098.3	804	180	130	600 x 0rise	350 x 27.2

RXC PRO

SIZE	A. HA	B. SA	C. TTL (HORIZONTAL)	D. TTL (C TO C)	E. HEAD TUBE LENGTH	F. ST LENGTH (C TO T)	G. ST LENGTH (C TO C)	H. BB DROP	I. CHAINSTAY LENGTH	J. FRONT CENTER	K. WHEEL BASE	L. STANDOVER	CRANK LENGTH	STEM	H-BAR	SEATPOST SIZE
15.5	71.0	74.5	560	546.3	120	394	333.1	40	426	625.2	1048	701	170	100	580 x 30rise	350 x 27.2
17.5	71.0	73.0	590	564.7	120	445	386	40	422	639.5	1058.3	731	175	110	580 x 30rise	350 x 27.2
19.5	71.0	73.0	620	594.3	130	495	435.8	40	422	669.8	1088.7	766	175	120	600 x 30rise	350 x 27.2
21.5	71.0	72.5	635	611.3	150	546	486.8	40	422	680	1098.9	804	175	130	620 x 30rise	350 x 27.2

RXC ELITE

SIZE	A. HA	B. SA	C. TTL (HORIZONTAL)	D. TTL (C TO C)	E. HEAD TUBE LENGTH	F. ST LENGTH (C TO T)	G. ST LENGTH (C TO C)	H. BB DROP	I. CHAINSTAY LENGTH	J. FRONT CENTER	K. WHEEL BASE	L. STANDOVER	CRANK LENGTH	STEM	H-BAR	SEATPOST SIZE
15.5	71.0	74.5	560	546.3	120	394	333.1	40	426	625.2	1048	701	170	100	580 x 30rise	350 x 27.2
17.5	71.0	73.0	590	564.7	120	445	386	40	422	639.5	1058.3	731	175	110	580 x 30rise	350 x 27.2
19.5	71.0	73.0	620	594.3	130	495	435.8	40	422	669.8	1088.7	766	175	120	600 x 30rise	350 x 27.2
21.5	71.0	72.5	635	611.3	150	546	486.8	40	422	680	1098.9	804	175	130	620 x 30rise	350 x 27.2

RXC

SIZE	A. HA	B. SA	C. TTL (HORIZONTAL)	D. TTL (C TO C)	E. HEAD TUBE LENGTH	F. ST LENGTH (C TO T)	G. ST LENGTH (C TO C)	H. BB DROP	I. CHAINSTAY LENGTH	J. FRONT CENTER	K. WHEEL BASE	L. STANDOVER	CRANK LENGTH	STEM	H-BAR	SEATPOST SIZE
15.5	71.0	74.5	560	546.3	120	394	333.1	40	426	625.2	1048	701	170	100	580 x 0rise	350 x 27.2
17.5	71.0	73.0	590	564.7	120	445	386	40	422	639.5	1058.3	731	175	110	580 x 0rise	350 x 27.2
19.5	71.0	73.0	620	594.3	130	495	435.8	40	422	669.8	1088.7	766	175	120	600 x 0rise	350 x 27.2
21.5	71.0	72.5	635	611.3	150	546	486.8	40	422	680	1098.9	804	175	130	600 x 0rise	350 x 27.2

JUMP SHOT

SIZE	A. HA	B. SA	C. TTL (HORIZONTAL)	D. TTL (C TO C)	E. HEAD TUBE LENGTH	F. ST LENGTH (C TO T)	G. ST LENGTH (C TO C)	H. BB DROP	I. CHAINSTAY LENGTH	J. FRONT CENTER	K. WHEEL BASE	L. STANDOVER	CRANK LENGTH	STEM	H-BAR	SEATPOST SIZE
15"	69.5	72.0	565	550.8	120	380	300	26	430	628.9	1058	701	175	40	640 x 25rise	250 x 31.6


STRAIGHT / DOUBLE SHOT

SIZE	A. HA	B. SA	C. TTL (HORIZONTAL)	D. TTL (C TO C)	E. HEAD TUBE LENGTH	F. ST LENGTH (C TO T)	G. ST LENGTH (C TO C)	H. BB DROP	I. CHAINSTAY LENGTH	J. FRONT CENTER	K. WHEEL BASE	L. STANDOVER	CRANK LENGTH	STEM	H-BAR	SEATPOST SIZE
15"	69.5	72.0	595	581.8	120	380	300	20	430	662	1091.4	710	175	40	680 x 50rise	350 x 31.6

2006 FELT MTB GEOMETRY CHART

A = Head Tube Angle
 B = Seat Tube Angle
 C = Top Tube Length (Horiz.)
 D = Top Tube Length (C - C)
 E = Head Tube Length
 F = Seat Tube Length (C - T)
 G = Seat Tube Length (C - C)
 H = BB Drop
 I = Chain Stay Length
 J = Front Center
 K = Wheel Base
 L = Stand Over

(Horiz.) = Horizontal
 (C - C) = Center to Center
 (C - T) = Center to Top



2006 FELT SHOT GEOMETRY CHART

A = Head Tube Angle
 B = Seat Tube Angle
 C = Top Tube Length (Horiz.)
 D = Top Tube Length (C - C)
 E = Head Tube Length
 F = Seat Tube Length (C - T)
 G = Seat Tube Length (C - C)
 H = BB Drop
 I = Chain Stay Length
 J = Front Center
 K = Wheel Base
 L = Stand Over

(Horiz.) = Horizontal
 (C - C) = Center to Center
 (C - T) = Center to Top

